## NAME

bashbug – report a bug in bash

## SYNOPSIS

**bashbug** [*--version*] [*--help*] [*email-address*]

## DESCRIPTION

**bashbug** is a shell script to help the user compose and mail bug reports concerning bash in a standard format. **bashbug** invokes the editor specified by the environment variable **EDITOR** on a temporary copy of the bug report format outline. The user must fill in the appropriate fields and exit the editor. **bashbug** then mails the completed report to *bug-bash@gnu.org*, or *email-address*. If the report cannot be mailed, it is saved in the file *dead.bashbug* in the invoking user's home directory.

The bug report format outline consists of several sections. The first section provides information about the machine, operating system, the bash version, and the compilation environment. The second section should be filled in with a description of the bug. The third section should be a description of how to reproduce the bug. The optional fourth section is for a proposed fix. Fixes are encouraged.

## ENVIRONMENT

**bashbug** will utilize the following environment variables if they exist:

**EDITOR**

Specifies the preferred editor. If **EDITOR** is not set, **bashbug** attempts to locate a number of alternative editors, including **emacs**. If **bashbug** cannot locate any of the alternative editors, it attempts to execute **vi**.

**HOME**

Directory in which the failed bug report is saved if the mail fails.

**TMPDIR**

Directory in which to create temporary files and directories.

## SEE ALSO

*bash*(1)

## AUTHORS

Brian Fox, Free Software Foundation
bfox@gnu.org

Chet Ramey, Case Western Reserve University
chet@po.cwru.edu