Contents

1 **sqlxx** 3
2 **CSQLResult::~CSQLResult** — ***SQL Result Destructor.*** 4
3 **CSQLResult::close** — ***Closes database connection.*** 5
4 **CSQLResult::getError** — ***Returns last error message.*** 6
5 **CSQLResult::query** — ***Query Database.*** 7
6 **CSQLResult::getNumCols** — ***Return number of columns.*** 8
7 **CSQLResult::getNumRows** — ***Return number of rows.*** 9
8 **CSQLResult::getColName** — ***Returns column name.*** 10
9 **CSQLResult::getColType** — ***Returns column type.*** 11
10 **CSQLResult::fetch** — ***Fetch a row of data.*** 12
11 **CSQLResult::get** — ***Returns column value as string.*** 13
12 **CSQLResult::get** — ***Returns column value as string.*** 14
13 **CSQLResult::getInt** — ***Returns column value as long integer.*** 15
14 **CSQLResult::getInt** — ***Returns column value as long integer.*** 16
15 **CSQLResult::getFloat** — ***Returns column value as float.*** 17
16 **CSQLResult::getFloat** — ***Returns column value as float.*** 18
17 **CSQLResult::isNull** — ***Determine if column value is NULL.*** 19
18 **CSQLResult::isNull** — ***Determine if column value is NULL.*** 20
19 **CSQL::CSQL** — ***SQL Constructor.*** 21
20 **CSQL::~CSQL** — ***SQL Destructor.*** 22
21 **CSQL::getError** — ***Get last error message.*** 23
22 **CSQL::addResult** — ***Connects a CSQLResult to this CSQL object.*** 24
23 **CSQL::delResult** — ***Disconnects a CSQLResult from this CSQL object.*** 25
24 **CSQL::setDSN** — ***Sets DSN.*** 26
25 **CSQL::setHostname** — ***Sets Hostname.*** 27
26 **CSQL::setSocket** — ***Sets Socket.*** 28
27 **CSQL::setPort** — ***Sets Port.*** 29
28 **CSQL::setPort** — ***Sets Port.*** 30
29 **CSQL::setDatabase** — ***Sets database name.*** 31
30 **CSQL::setDriver** — ***Sets ODBC driver.*** 32
31 **CSQL::setUsername** — ***Sets database username.*** 33
32 **CSQL::setPassword** — ***Sets database password.*** 34
33 **CSQL::setOptions** — ***Sets database options.*** 35
34 **CSQL::setType** — ***Sets database type.*** 36
35 **CSQL::getDSN** — ***Returns DSN.*** 37
36 **CSQL::getHostname** — ***Returns Hostname.*** 38
37 **CSQL::getSocket** — ***Returns Socket.*** 39

38 **CSQL::getPort** — ***Returns Port.*** 40
39 **CSQL::getPortN** — ***Returns Port.*** 41
40 **CSQL::getDatabase** — ***Returns database name.*** 42
41 **CSQL::getDriver** — ***Returns ODBC driver.*** 43
42 **CSQL::getUsername** — ***Returns database username.*** 44
43 **CSQL::getPassword** — ***Returns database password.*** 45
44 **CSQL::getOptions** — ***Returns ODBC options.*** 46
45 **CSQL::getType** — ***Returns database type.*** 47
46 **CSQL::connect** — ***Connect to database.*** 48
47 **CSQL::disconnect** — ***Disconnects from database.*** 49
48 **CSQL::isConnected** — ***Determine if connected.*** 50
49 **CSQL::openQuery** — ***Opens an SQL Query.*** 51
50 **CSQL::execQuery** — ***Execute SQL query.*** 52
51 **CSQL::closeQuery** — ***Closes SQL query.*** 53
52 **CSQL::getNewID** — ***Returns next available Primary key.*** . 54
53 **CSQL::getQueries** — ***Returns vector with active queries.*** .. 55
54 **CSQL::countQueries** — ***Count active queries.*** 56

1 sqlxx

This library contains C++ classes for easy database access via ODBC using libiodbc2 or via native access. Currently the native access to mysql and postgresql databases is implemented.

Author: Klaus Reimer <k@ailis.de>
Version: 2.1.0

2

CSQLResult::~CSQLResult (void)

SQL Result Destructor.

SQL Result Destructor. This is the destructor of the SQL Result. It calls CSQL::close() to close the database connection.

3

void **CSQLResult::close** (void)

Closes database connection.

Closes database connection. This method closes the database connection and frees all allocated memory.

4

string **CSQLResult::getError** (void)

Returns last error message.

Returns last error message. This method returns the last error message of the SQL Result.

5

void **CSQLResult::query** (const string &sQuery)

Query Database.

Query Database. This method sends the SQL query **sQuery** to the database. You don't need to use this method on your own. Use CSQL::openQuery() instead.

6

unsigned int **CSQLResult::getNumCols** (void)

Return number of columns.

Return number of columns. This method returns the number of columns of the current SQL Result.

7

unsigned long **CSQLResult::getNumRows** (void)

Return number of rows.

Return number of rows. This method returns the number of rows of the current SQL Result.

8

string **CSQLResult::getColName** (const unsigned int iIndex)

Returns column name.

Returns column name. Return the name of the column with the index **iIndex**.

9

int **CSQLResult::getColType** (const unsigned int iIndex)

Returns column type.

Returns column type. Returns the type of the column with index **iIndex**. The meaning of the type is database dependent.

10

bool **CSQLResult::fetch** (void)

Fetch a row of data.

Fetch a row of data. This method fetches a row of data from the current SQL Result.

11

string **CSQLResult::get** (const unsigned int iIndex)

Returns column value as string.

Returns column value as string. Returns the value of the column with index **iIndex** as string.

12

string **CSQLResult::get** (const string sField)

Returns column value as string.

Returns column value as string. Returns the value of the column named **sField** as string.

13

long **CSQLResult::getInt** (const unsigned int iIndex)

Returns column value as long integer.

Returns column value as long integer. Returns the value of the column with index **iIndex** as long integer.

14

long **CSQLResult::getInt** (const string sField)

Returns column value as long integer.

Returns column value as long integer. Returns the value of the column named **sField** as long integer.

15

float **CSQLResult::getFloat** (const unsigned int iIndex)

Returns column value as float.

Returns column value as float. Returns the value of the column with index **iIndex** as long float.

16

float **CSQLResult::getFloat** (const string sField)

Returns column value as float.

Returns column value as float. Returns the value of the column named **sField** as long float.

17

bool **CSQLResult::isNull** (const unsigned int iIndex)

Determine if column value is NULL.

Determine if column value is NULL. Returns true if the value of the column with index **iIndex** is NULL. Returns false if not.

18

bool **CSQLResult::isNull** (const string sField)

Determine if column value is NULL.

Determine if column value is NULL. Returns true if the value of the column named **sField** is NULL. Returns false if not.

19

CSQL::CSQL (void)

SQL Constructor.

SQL Constructor. This is the constructor of the class CSQL. It initializes the SQL object with empty values.

20

CSQL::~CSQL (void)

SQL Destructor.

SQL Destructor. This is the destructor of the CSQL class. It automatically disconnects all open database connections and frees all allocated memories of all connected CSQLResult objects.

21

string **CSQL::getError** (void* Result=NULL)

Get last error message.

Get last error message. This method returns the last error message. If no parameter is given the last database related error message is returned. If a Pointer to a CSQLResult object is specified, the last error message of this SQLResultObject is returned. Don't use this method if possible. Catch the sqlxx_error exceptions which already contains the complete error message.

22

void **CSQL::addResult** (CSQLResult* Result)

Connects a CSQLResult to this CSQL object.

Connects a CSQLResult to this CSQL object. This method is used internally to connect a CSQLResult object to this CSQL object. THe connected CSQLResult objects are freed automatically by the CSQL destructor.

23

void **CSQL::delResult** (CSQLResult* Result)

Disconnects a CSQLResult from this CSQL object.

Disconnects a CSQLResult from this CSQL object. This method is used internally to disconnect a CSQLResult object from this CSQL object. THe connected CSQLResult objects are freed automatically by the CSQL destructor.

24

void **CSQL::setDSN** (const string &sNewDSN)

Sets DSN.

Sets DSN. Sets the DSN to **sNewDSN**. The DSN is only used by ODBC connections.

25

void **CSQL::setHostname** (const string &sNewHostname)

Sets Hostname.

Sets Hostname. Sets Hostname to **sNewHostname**.

26

void **CSQL::setSocket** (const string &sNewSocket)

Sets Socket.

Sets Socket. Sets Socket to **sNewSocket**.

27

void **CSQL::setPort** (const string &sNewPort)

Sets Port.

Sets Port. Sets Ports to **sNewPort**. Use this method if you want to specify the port address as a string.

28

void **CSQL::setPort** (const unsigned int iNewPort)

Sets Port.

Sets Port. Sets Ports to **sNewPort**. Use this method if you want to specify the port address as an integer.

29

void **CSQL::setDatabase** (const string &sNewDatabase)

Sets database name.

Sets database name. Sets database name to **sNewDatabase**.

30

void **CSQL::setDriver** (const string &sNewDriver)

Sets ODBC driver.

Sets ODBC driver. Sets odbc driver to **sNewDriver**. This value is only used for ODBC connections

31

void **CSQL::setUsername** (const string &sNewUsername)

Sets database username.

Sets database username. Sets database username to **sNewUsername**.

32

void **CSQL::setPassword** (const string &sNewPassword)

Sets database password.

Sets database password. Sets database password to **sNewPassword**.

33

void **CSQL::setOptions** (const string &sNewOptions)

Sets database options.

Sets database options. Sets database options to **sNewOptions**. These options are only used by ODBC connections. Your ODBC driver documentation will tell you what options are possible.

34

void **CSQL::setType** (const unsigned short iNewType)

Sets database type.

Sets database type. Sets database type to **iNewType**. This can be SQLXX_MYSQL, SQLXX_POSTGRES or SQLXX_ODBC. But this is dependent on how you have compiled the sqlxx library.

35

string **CSQL::getDSN** (void)

Returns DSN.

Returns DSN. Returns the DSN.

36

string **CSQL::getHostname** (void)

Returns Hostname.

Returns Hostname. Returns the Hostname.

37

string **CSQL::getSocket** (void)

Returns Socket.

Returns Socket. Returns the Socket.

38

string **CSQL::getPort** (void)

Returns Port.

Returns Port. Returns the port address as string.

39

unsigned int **CSQL::getPortN** (void)

Returns Port.

Returns Port. Returns the port address as unsigned integer.

40

string **CSQL::getDatabase** (void)

Returns database name.

Returns database name. Returns the database name.

41

string **CSQL::getDriver** (void)

Returns ODBC driver.

Returns ODBC driver. Returns the filename to the ODBC driver.

42

string **CSQL::getUsername** (void)

Returns database username.

Returns database username. Returns the database username.

43

string **CSQL::getPassword** (void)

Returns database password.

Returns database password. Returns the database password.

44

string **CSQL::getOptions** (void)

Returns ODBC options.

Returns ODBC options. Returns the ODBC options.

45

unsigned short **CSQL::getType** (void)

Returns database type.

Returns database type. Returns the database type.

46

void **CSQL::connect** (void)

Connect to database.

Connect to database. This method inititates the connection to the database.

47

void **CSQL::disconnect** (void)

Disconnects from database.

Disconnects from database. This methode closes the connection to the database.

48

bool **CSQL::isConnected** (void)

Determine if connected.

Determine if connected. This method returns true if the database connection is established. False if not.

49

CSQLResult* **CSQL::openQuery** (const string &sQuery, const int iBuffer-Size=1024)

Opens an SQL Query.

Opens an SQL Query. This method opens a new SQL query **sQuery** and returns a pointer to a CSQLResult object.

50

void **CSQL::execQuery** (const string &sQuery)

Execute SQL query.

Execute SQL query. This method executes the SQL query **sQuery**.

51

void **CSQL::closeQuery** (const CSQLResult* DBResult)

Closes SQL query.

Closes SQL query. Closes the SQL query **DBResult**.

52

long **CSQL::getNewID** (const string &sTable, const string &sIDField)

Returns next available Primary key.

Returns next available Primary key. This method returns the next available primary key value for the field **sIDField** in table **sTable**

53

vector< CSQLResult * > & **CSQL::getQueries** (void)

Returns vector with active queries.

Returns vector with active queries. This method returns a vector with pointers to all active queries of this CSQL object.

54

int **CSQL::countQueries** (void)

Count active queries.

Count active queries. Returns the number of active SQL queries of this CSQL object.