UCRL-MA-108975 Rev. 1

PDBDiff User's Manual

for
PDBDiff Version 2.0

Stewart A. Brown
Dennis Braddy

Lawrence Livermore National Laboratory

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

Work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract W-7405-Eng-48.

Table of Contents

1.0 Introduction....1
2.0 Data Files with PDBDiff....2
3.0 PDBDiff Syntax....3
4.0 Starting PDBDiff....5
5.0 PDBDiff Commands....6
6.0 Default State....13
7.0 Other PACT Documents....14

1.0 Introduction

The PACT system provides a number of tools for working with PDB files in a fairly generic fashion. In particular, PDBDiff compares the contents of two PDB files and displays the differences (in a manner similar but not identical to the UNIX utility **diff**). PDBDiff can also be run in an interactive mode which allows you to compare two PDB files on a variable by variable or even leaf by leaf basis.

PDBDiff is an SX program. SX is the SCHEME dialect of the LISP programming language with PACT extensions. The extensions provide functionality for graphics, binary data handling, and other areas of functionality.

PDBDiff has a **help** command which provides information about available commands.

Note: The files compared may have been created on or for different target machines. Consequently, a given data type may be represented differently in the two files. In this event values are compared to the precision in the first file, or the precision in the second file, or the precision you specify, whichever is least.

2.0 Data Files with PDBDiff

PDBDiff can be used to compare the contents of any two PDB files. It compares files entry by entry. In the most commonly used mode of use it has no knowledge of the semantics of the data in the files it compares.

2.1 PVA Files

There is a special kind of PDB file called a PVA (Portable Visualization and Analysis) file which contains data sets structured in a particular way so as to completely specify all information necessary to visualize the data set or to perform mathematical operations such as differentiation and integration on it. PANACEA codes produce PVA files as the PACT supported option for data output. PDBDiff can compare these files in a special way. Since it has complete information about the data sets, it can compare data sets which represent the same quantity but, potentially, with different amounts of information. For example, two runs of a numerical simulation code might compute a given quantity but with different resolution on the computational mesh. PDBDiff can compare these data sets by interpolating them to a common domain and computing the difference measure:

$$\delta = \int \left(\frac{|\|a\| - \|b\||}{\|a\| + \|b\|} \right) dV$$

If the difference measure is less than a specified threshold, PDBDiff goes on to the next mapping in the file. However, if the difference measure exceeds the threshold, the two mappings, a and b, are displayed in separate windows along with the integrand above in its own window. The user is prompted to specify whether or not the differences are acceptable. In this way PDBDiff can be used as an aide to developing simulation codes and testing them.

3.0 PDBDiff Syntax

PDBDiff uses a slightly different data description syntax than PDBLib. With PDBLib variable names and names of members of structures cannot contain the characters: ".", "(", ")", "[", and "]". The characters "(", ")", "[", and "]" are used in array reference and dimension definition expressions. In PDBDiff, "(" and ")" CANNOT be used in variable reference expressions because they are special characters for PDBDiff. For example,

```
print a(2)
```

is illegal and results in an error. The legal expression is:

```
print a[2]
```

Other examples of legal expressions are:

```
print a.b[3,2]
print a.b[3][2]
print a[3].b[2][5].c
print a[3].b[2][3].c[3:4,5:50:10]
```

The first two forms are not identical. In the first form an element of a two dimensional array is being referenced. In the second form, the third element of the fourth array of arrays is being referenced (assuming zero based indexing in the definition of the b member of a).

For completeness and clarity in the following discussion, an index expression is defined as:

index expression := [*index list*]
index list := *index* | *index, index list*
index := *simple index* |
index-min : index-max | (*)
index-min : index-max : increment *(*)*
simple index := *integer*
index-min := *integer*
index-max := *integer*
increment := *integer*

If an index expression uses either of the two starred forms it is said to be a hyper-index expression. A hyper-index expression implies more than one data item. Only the terminating index expression in a data reference may be a hyper-index expression. An index expression is said to dereference an indirection (or pointer or array). For each level of indirection a suitable index expression dereferences the desired data.

For example, this means that a variable defined as:

```
char **s
```

is said to have two levels of indirection and can have parts accessed as follows:

print s	prints the entire item
print s[2]	prints the third character array of s
print s[3][10]	prints the eleventh character of the fourth character array of s

In the above example a zero based index is assumed.

When referring to part of a variable, especially a structured variable, the terminal node must be of primitive type or a structure containing no indirections and whose descendant members contain no indirections. Furthermore, the path to the desired part must contain one array reference for each level of indirection traversed.

4.0 Starting PDBDiff

On UNIX systems a shell script called **pdbdiff** is provided; it starts up SX and loads the PDBDiff SCHEME forms. You must add a line to your **.cshrc** or **.profile** file that defines the environment variable SCHEME. This variable tells SX where to find the PDBDiff program. Consult your system administrator or some other knowledgeable source to find where this is kept. If, for example, the directory **/usr/local/scheme** contains the PDBDiff program file, add the line:

```
setenv SCHEME /usr/local/scheme
```

to your **.cshrc** or **.profile** file.

Usage: pdbdiff [-a] [-b *n*] [-d] [-i] [-l] [-p *f*] [-s] [-v] *pdb-file1 pdb-file2*

Options:

a - display all elements if any differ

b - number of mantissa bits to use in floating point comparisons

d - compare floating point types of differing precision

i - enter interactive mode

l - compare fixed point types of differing precision

p - fractional decimal precision to use in floating point comparisons

s - display only differing elements (default)

v - compare PVA files (batch mode only currently)

5.0 PDBDiff Commands

In this section the PDBDiff commands are listed alphabetically. Each command is given with a brief description of its function and examples of its usage. The examples are intended to illustrate the various ways of invoking each command.

CD

Change the current file directory in the designated file. The first file is designated by **1**, **a**, or **first** and the second file is designated by **2**, **b**, or **second**. If neither file is specified the file directory is changed for both files. The new directory may be specified by either a relative path or a full path.

Usage: cd [*directory*] [1 | a | first | 2 | b | second]

Examples:

cd /zoo/mammals

cd ../reptiles first

cd

CLOSE

Close the current pair of files.

Usage: close

DESC

Describe the named variable or structure member in the designated file. The first file is designated by **1**, **a**, or **first** and the second file is designated by **2**, **b**, or **second**. To get a description of part of a variable or structure member, qualify the name with index expressions (see the PDBDiff Syntax section for a discussion of index expressions).

Usage: desc *variable* | *structure-member* [1 | a | first | 2 | b | second]

Examples:

desc Mapping1

desc Mapping1.range 1

desc baz second

DIFF

Compare the values of the named variable(s) or structure member(s) in the two open files. If two variable names are provided, the values of the first variable in the first file will be compared with the values of the second variable in the second file. To compare part of a variable or structure member, qualify the name with index expressions (see the PDBDiff Syntax section for a discussion of index expressions). You may specify the format of the output with the **mode** and **set** commands.

Usage: diff *variable* | *structure-member* [*variable* | *structure-member*]

Examples:

diff Mapping3

diff foo.bar

diff abc def

END

End the PDBDiff session.

Usage: end

FILE

Describe a PDB file. The first file is designated by **1**, **a**, or **first** and the second file is designated by **2**, **b**, or **second**.

Usage: file [1 | a | first | 2 | b | second]

Examples:

file

file second

FORMAT

Set the printing format for a specified data type. If the argument specifying the type has '1' or '2' appended, then the new format is applied only to arrays shorter than **array-length** or to arrays longer than or equal to **array-length**, respectively. Otherwise, the format applies to both. Invoking the format command with the single argument, **default**, causes the formats for all types to be reset to their default values. The *format* argument must be a Standard C I/O Library format string. Double quotes are only necessary if the format string contains embedded blanks. See the **set** command for more information about the **array-length** display control parameter. This command overrides the settings of the **decimal-precision** and **bits-precision** display control parameters.

Usage: format integer[1 | 2] | long[1 | 2] | float[1 | 2] |
double[1 | 2] | short[1 | 2] | char[1 | 2] *format*

Usage: format default

Examples:

format double %12.5e
format double2 %10.2e
format char "%s "
format default

HELP

Print a list of the available commands or information about the specified command.

Usage: help [*command*]

Examples:

help
help open

LS

List the names of variables, links, and directories in the designated file. The first file is designated by **1**, **a**, or **first** and the second file is designated by **2**, **b**, or **second**. If neither file is specified the information is listed for both files. Directories have a terminal slash. An optional selection pattern may be specified. Each '?' in the pattern matches any single character. Each '*' in the pattern matches any string of zero or more characters. An optional type qualifier may also be specified in order restrict the list to a given type. A type qualifier of '*' may be used to match all types. Both a selection pattern and a type qualifier must be specified if you wish to designate a file.

Usage**:** ls [*pattern* [*type* [1 | a | first | 2 | b | second]]]

Examples:

ls dir1/curve*

ls var? integer second

ls * Directory

ls * * first

MODE

Set the print mode for arrays and structures.

Display modes are:

full-path - the full path name is printed at each branch, e.g. foo.bar[3].baz

indent - indent 4 spaces at each branch (default)

tree - display as a tree (lines connecting branches)

Type display is controlled by:

no-type - turns off the display of types (default)

type - displays the type of each item and branch

Display of recursive structures is controlled by:

recursive - indent each level of recursive structures

iterative - number each level of recursive structures (default)

Display of differing elements is controlled by:

individual - display only differing elements (default)

display-all - display all elements if even one differs

Usage: mode full-path | indent | tree | no-type | type |
recursive | iterative | individual | display-all

Example:

mode no-type

OPEN

Open a new pair of files.

Usage: open *filename1 filename2*

Example:

open foo.s00 bar.s00

PRINT

Print out all or part of the specified variable or structure member from the first or second file. The first file is designated by **1**, **a**, or **first** and the second file is designated by **2**, **b**, or **second**. To print part of a variable or structure member, qualify the name with index expressions (see the PDBDiff Syntax section for a discussion of index expressions).

Usage: print *variable* | *structure-member* [1 | a | first | 2 | b | second]

Examples:

Mapping2 first

print Mapping2.range.elements[1] 2

a[5,10:20,1:8:3]

print a.b[3].c[5,10:20,1:8:3] b

PROMOTE

Promote lower precision types in the specified class or classes to higher precision to permit comparison, if necessary. Turn off promotion for classes not specified. The default is no promotion.

Usage: promote [fixed] [float]

Examples:

promote

promote fixed

promote float

promote fixed float

PWD

Print the current file directory for the designated file.The first file is designated by **1**, **a**, or **first** and the second file is designated by **2**, **b**, or **second**. If neither file is specified the current file directory will be printed for both files. NOTE: If the current file directory is the same for both files, it will only be printed once.

Usage: pwd [1 | a | first | 2 | b | second]

Examples:

pwd

pwd first

SET

Set the value of some display parameters. Parameters:

line-length - number of array elements per line

array-length - for arrays shorter than value, label each element individually

bits-precision - number of mantissa bits compared in floating point numbers

decimal-precision - limit on the fractional difference reported

Usage: set line-length | array-length | bits-precision | decimal-precision *value*

Examples:

set line-length 3

set array-length 20

set bits-precision 10

set decimal-precision 1.0e-6

STRUCT

Describe the named data type in the specified file. The first file is designated by **1**, **a**, or **first** and the second file is designated by **2**, **b**, or **second**.

Usage: struct *data-type* [1 | a | first | 2 | b | second]

Examples:

struct double 1

struct PM_mapping second

TRANSCRIPT

Toggle a transcript of the PDBDiff session. The name of the transcript file may be specified when the transcript is activated. A file named **pdbdiff.trn** will contain the transcript of the session if no name is given.

Usage: transcript [*filename*]

Examples:

transcript

transcript foo.bar

TYPES

List the data types in the designated file.The first file is designated by **1**, **a**, or **first** and the second file is designated by **2**, **b**, or **second**. If neither file is specified the data types will be printed for both files.

Usage: types [1 | a | first | 2 | b | second]

Examples:

types

types second

6.0 Default State

The initial state of PDBDiff is:

- mode indent
- mode no-type
- mode iterative
- mode individual
- set line-length 2
- set array-length 4
- set bits-precision 128 (i.e. use all mantissa bits in floating point comparisons)

7.0 Other PACT Documents

Interested readers may wish to refer to the other PACT documents which describe the data structures and functionality underlying the more common PDB files upon which PDBDiff operates. The PANACEA, PGS, and PDBLib manuals are of special interest to people who wish to generate and view data files with PACT.

The list of PACT Documents is:

PACT User's Guide, UCRL-MA-112087

SCORE User's Manual, UCRL-MA-108976 Rev.1

PPC User's Manual UCRL-MA-108964 Rev.1

PML User's Manual, UCRL-MA-108965 Rev.1

PDBLib User's Manual, M-270 Rev.2

PGS User's Manual, UCRL-MA-108966 Rev.1

PANACEA User's Manual, M-276 Rev.2

ULTRA II User's Manual, UCRL-MA-108967 Rev.1

PDBDiff User's Manual, UCRL-MA-108975 Rev.1 (this document)

PDBView User's Manual, UCRL-MA-108968 Rev.1

SX User's Manual, UCRL-MA-112315

Symbols

% 8
%s 8
(....3
) 3
* 9
. 3
.cshrc 5
.profile 5
/usr/local/scheme 5
? 9

Numerics

1 ....6, 7, 8, 9, 10, 11, 12
2 ....6, 7, 8, 9, 10, 11, 12

A

-a 5
a 6, 7, 9, 10, 11, 12
array- length 8
array-length 11, 13
arrays 9

B

-b 5
b 6, 7, 9, 10, 11, 12
bits-precision 8, 11, 13
blanks 8
branch 9

C

CD 6
Change the current file directory 6
char 8
class 10
CLOSE 6
Commands 6
compare PVA files 5
Compare the values 7
control parameters 8
current file directory 11

D

-d 5
Data Files with PDBDiff 2
data reference 3
data type 8, 11
decimal precision 5
decimal-precision 8, 11
Default 13
default 8, 9
Default State 13
dereference 3
DESC 6
Describe a PDB file 7
Describe the named data type 11
Describe the named variable 6
DIFF 7
diff 1
difference measure 2
directory 6, 11
display all elements 9
display all elements if any differ 5
display control parameters 8
Display modes 9
Display of differing elements 9
display only differing elements 5, 9
display parameters 11
display-all 9
documents 14
double 8
Double quotes 8

E

e 8
each element labeled 11
embedded blanks 8
END 7
environment variable 5

F

FILE 7
first 6, 7, 9, 10, 11, 12
fixed 10
float 8, 10
floating point comparisons 5, 13
floating point numbers 11
FORMAT 8
format of the output 7
fractional decimal precision 5
fractional difference 11
full path 6
full-path 9

H

HELP 8
help 1
hyper-index expression 3

I

-i 5
increment 3
indent 9, 13
index 3
index expression 3
index expressions 6, 7, 10
index list 3
index-max 3
index-min 3
indirection 3, 4
individual 9, 13
initial state 13
integer 8

interactive mode 1, 5
Introduction 1
iterative 9, 13

L

-l 5
level of indirection 3
levels of indirection 4
line-length 11, 13
LISP programming language 1
List the names of variables 9
List the types 12
long 8
LS 9

M

mantissa bits 13
mantissa bits compared 11
mantissa bits to use 5
manuals 14
member 6, 7, 10
members of structures 3
MODE 9
mode 1, 7, 13

N

names of members of structures 3
no-type 9, 13
number of array elements per line 11
number of mantissa bits compared 11
number of mantissa bits to use 5

O

OPEN 10
Options 5
output 7

P

-p 5
PACT 1, 14
PACT Documents 14
PANACEA 2, 14
parameters 8, 11
path name 9
pattern 9
PDB files 1, 14
PDBDiff 1, 5
pdbdiff 5
PDBDiff Commands 6
PDBDiff Syntax section 6, 7, 10
pdbdiff.trn 12
PDBLib 3, 14
PDBView Syntax 3
PGS 14
pointer or array 3
Portable Visualization and Analysis 2
precision 1, 5, 10
PRINT 10
Print a list of the available commands 8
print mode 9
print part of a variable 10
Print the current file directory 11
printing format 8
PROMOTE 10
PVA 2
PVA Files 2
PWD 11

Q

quotes 8

R

recursive 9
recursive structures 9
relative path 6

S

-s 5
SCHEME 1, 5
second 6, 7, 9, 10, 11, 12
selection pattern 9
SET 11
set 7, 8, 13
Set the print mode 9
Set the printing format 8
setenv 5
short 8
simple index 3
special 2
Starting PDBDiff 5
STRUCT 11
structure member 6, 7, 10
structures 3, 9
SX 1, 5
syntax 3

T

target machines 1
terminating index expression 3
threshold 2
Toggle a transcript 12
TRANSCRIPT 12
transcript file 12
transcript of the session 12
tree 9
type 8, 9
type qualifier 9
TYPES 12
types of differing precision 5

U

UNIX 1
use all mantissa bits 13

V

-v 5
variable names 3