NAME

mboxpath – ZMailer utility to show user's mailbox path

SYNOPSIS

mboxpath [**–D[D]**] [**–P[P]**] [**–X[X]**] [**–d** *dirpath*] *username*

DESCRIPTION

mboxpath is a ZMailer utility program to be used when local user directories have been scattered around, and it is desired to have user's shell environment variable **MAIL** be set to where ever his/her UNIX mailbox file is.

This does only manage scattering under common –*d dirpath* directory prefix, but usually that is sufficient.

OPTIONS

–d *dirpath*
: See *mailbox*(8).

–D[D] See *mailbox*(8).

–P[P] See *mailbox*(8).

–X[X] See *mailbox*(8).

USAGE

This is intended for system-wide startup script usage with code something like following for sh:

MAIL=‘mboxpath –P $USER‘

It is important to use SAME options here as are used at running the mailbox program.

ENVIRONMENT

The default location for user mailbox files depends per system, but one of them is: **/var/mail**. This may be modified by setting the variable **MAILBOX** in **/etc/zmailer.conf** to the directory containing user mailbox files, for example **/usr/spool/mail**. This is best done in the ZMailer SiteConfig file.

This program outputs the **likely** mailbox location to the stdout, it does not go and see if there is anything.

FILES

/etc/zmailer.conf
/var/mail (MAILBOX)

SEE ALSO

mailbox(8), scheduler(8), comsat(8C), biff(1), flock(2), Mail(1)

AUTHOR

This program authored and copyright by:
Matti Aarnio <mea@nic.funet.fi>